

PRODUCT-DETAILS

CM-PFE

CM-PFE Phase sequence monitoring relay 1c/o, L1-L2-L3=208-440VAC



General Information

Extended Product Type	CM-PFE
Product ID	1SVR550824R9100
EAN	4013614348044
Catalog Description	CM-PFE Phase sequence monitoring relay 1c/o, L1-L2-L3=208-440VAC
Long Description	The CM-PFE relay is from the CM three-phase monitors range. This relay operates with a rated control supply voltage / three-phase measuring voltage of 208-440 V AC and has a 1 c/o output (closed circuit principle) with contacts rated at 250 V / 4 A. The CM-PFE monitors the phase loss and phase sequence. The corresponding threshold values are fixed. The relay is suitable for monitoring of three phase mains.

Ordering

EAN	4013614348044
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112231D0201
Instructions and Manuals	1SVC550510M0002
CAD Dimensional	2CDC001079B0201

Drawing

Dimensions

Product Net Width	22.5 mm
Product Net Height	78 mm
Product Net Depth / Length	78.5 mm
Product Net Weight	0.068 kg

Technical

Function	Phase failure detection Phase sequence monitoring
Sub-Function	Phase loss
Sub-Function 2	Phase sequence
Measuring Range	(L-L) 208 ... 440 V AC
Time Range	500 ms start-up delay 500 ms tripping delay
Rated Control Supply Voltage (U _s)	(L-L) 208 ... 440 V AC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	1 c/o (SPDT) contact
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Rated Impulse Withstand Voltage (U _{imp})	Input Circuit 6 kV
Rated Insulation Voltage (U _i)	Input Circuit / Output Circuit 600 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Connecting Capacity	Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible 2x 1 ... 1.5 mm ² Rigid 2x 0.75 ... 1.5 mm ²
Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	10 mm
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 250 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible with Ferrule 2x 18-16 AWG Flexible 2x 18-16 AWG Rigid 2x 18-16 AWG
Tightening Torque UL/CSA	7.08 in-lb
Pilot Duty UL/CSA	B300

Environmental

Ambient Air Temperature	Operation -20 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	CB_DK-8880
CCC Certificate	CCC_2013010303605960
CQC Certificate	CQC2013010303605960
cUL Certificate	cUL508_E140448
Declaration of Conformity - CCC	2020980303000202
Declaration of Conformity - CE	1SVD981026-00
Declaration of Conformity - UKCA	1SVD981026-10
EAC Certificate	EAC_RU_C-DE.ME77.B.03206
Instructions and Manuals	1SVC550510M0002
RoHS Information	1SVD981026-00
UL Certificate	UL508_E140448

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	23 mm
Package Level 1 Depth / Length	82 mm
Package Level 1 Height	82 mm
Package Level 1 Gross Weight	0.08 kg
Package Level 1 EAN	4013614348044

Classifications

Object Classification Code	B
ETIM 7	EC001441 - Phase monitoring relay
ETIM 8	EC001441 - Phase monitoring relay
ETIM 9	EC001441 - Phase monitoring relay
eClass	V11.0 : 27371803

UNSPSC	39122332
E-Number (Finland)	3580833
E-Number (Sweden)	3860173

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Three Phase Monitors

