


Item		Strip LED SMD 2835 276LED/M		Photoes	
Input Voltage		AC220V			
Frequency Range		50-60Hz			
Total Harmonic Distortion		<10			
Power Factor		0.9			
Power Efficiency		92%			
Working Voltage		AC220-240V			
LED Amount		276PCS/M			
LED Consumption		8%			
System Consumption		8%			
LED Luminous Efficiency		40LM/W			
LED Lumen		16-18LM			
LED Initial Flux	DAYLIGHT	4968LM/M			
	Neutral White	4968LM/M			
	WARM WHITE	4968LM/M			
Lamp's Efficiency		98%			Cuper Light
Average luminance	2m				Size
	3m				
	4m	√			
Luminance Area	2m				
	3m				
	4m	√			
Luminance Uniformity					
Color Temperature	Daylight	6000-6500K			
	Neutral White	4200K			
	Warm white	3000-3200K			
Color Rendering Index	Daylight	70			
	Neutral White	70			
	Warm white	70			
Light Distribution		symmetry rectangle light spot			
The Angle Of The Light		120°			
The Bean Of The Light					
Light Design					
Junction Temperature		45°C		Photo of lighting	
Working Temperature		-C20°C ~ 40°C			
Storage Temperature		0°C ~ 30°C			
IP Grade		IP44			
Working Life-span		50000HOURS			
Power Line		15A/1000VAC 0.5mm ² PVC			
Connect Wire					
The Color of The Lamp Shell		transparent			
Packing in Carton		100met/carton NW: 17.5 kgs GW: 18.2 kgs			
Certificate		CE			

33×33×29CM

