


Item		Strip LED SMD 5050 R.G.B 144LED/ M	
Input Voltage		AC220V - 240V	
Frequency Range		50-60Hz	
Total Harmonic Distortion		<10	
Power Factor		0.9	
Power Efficiency		92%	
Working Voltage		AC220-240V	
LED Amount		144PCS/M	
LED Consumption		8%	
System Consumption		8%	
LED Luminous Efficiency		60LM/W	
LED Lumen		16-18LM	
LED Initial Flux	DAYLIGHT	2592LM/M	
	WARM WHITE	2592LM/M	
Lamp's Efficiency		98%	
Average luminance	2m		
	3m		
	4m	√	
Luminance Area	2m		
	3m		
	4m	√	
Luminance Uniformity			
Color	RGB		
Color Rendering Index	DAYLIGHT	70	
	WARM WHITE	70	
Light Distribution		symmetry rectangle light spot	
The Angle Of The Light		120°	
The Bean Of The Light			
Light Design			
Junction Temperature		45°C	
Working Temperature		-C20°C ~ 40°C	
Storage Temperature		0°C ~ 30°C	
IP Grade		IP44	
Working Life-span		50000HOURS	
Power Line		15A/1000VAC 0.5mm ² PVC	
Connect Wire			
The Color of The Lamp Shell		transparent	
Packing in Carton		50met/carton NW: 10 kgs GW: 10.5 kgs	
Certificate		CE	
		Photos	
			
		Cuper Light	
		Size	
		32×32×22CM	
		Photo of lighting	
		