

Product data sheet

Specifications



iDPN - circuit breaker - iDPN N - 3P + N - 32A - C curve

A9N21600

! Discontinued on: 14 October 2021

! Discontinued

Main

Range of product	Clario
Range	Clario
Product name	IDPN
Product or component type	Miniature circuit-breaker
Device short name	iDPN N
Device application	Distribution
Poles description	3P + N
Number of protected poles	3
Neutral position	Left
[In] rated current	32 A
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	6000 A Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1
Suitability for isolation	Yes

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230 V AC 50/60 Hz between phase and neutral 400 V AC 50/60 Hz between phases
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	6000 A 100 % x Icn at 400 V AC 50/60 Hz conforming to EN/IEC 60898-1
Limitation class	3 conforming to EN/IEC 60898-1
[Ui] rated insulation voltage	400 V AC 50/60 Hz conforming to IEC 60947-2
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-2
Contact position indicator	Yes
Control type	Toggle

Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	78 mm
Net weight	322 g
Colour	White
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Locking options description	Padlocking device
Connections - terminals	Tunnel type terminals downstream 0.33...10 mm ² flexible Tunnel type terminals downstream 0.75...16 mm ² rigid Tunnel type terminals upstream 0.33...10 mm ² flexible Tunnel type terminals upstream 0.75...16 mm ² rigid
Wire stripping length	13 mm
Tightening torque	2 N.m
Earth-leakage protection	Separate block

Environment

Standards	EN/IEC 60898-1
IP degree of protection	IP20 conforming to IEC 60529
Pollution degree	3 conforming to IEC 60947-1
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.3 cm
Package 1 Width	7.4 cm
Package 1 Length	8.8 cm
Package 1 Weight	340 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
-----------------	-----------

Recommended replacement(s)

A9N21600 is replaced by:

1x



Miniature circuit breaker (MCB), Acti9 iC40N, 3P+N, 32A, C curve, 6000A (IEC/EN 60898-1), 10kA (IEC/EN 60947-2)
A9P54732
