

Product data sheet

Specifications



Pragma flush enclosure - IP40 - 2 x 13 modules - without door

PRA25213

! To be discontinued on: 31 October 2023

! To be discontinued

Main

| | |
|-----------------------------|---|
| Range | Pragma |
| Product or component type | Enclosure |
| Enclosure type | Distribution enclosure |
| Width | 366 mm wall: 396 mm outside: |
| Height | 480 mm wall: 510 mm outside: |
| Depth | 86 mm wall: 21 mm outside: |
| Nb of 18 mm modules per row | 13 |
| Nb of horizontal rows | 2 |
| Electrical insulation class | Class II Double insulation |
| Provided equipment | 2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip |
| Type of door | Without |

Complementary

| | |
|-------------------------------|--|
| Enclosure mounting | Flush |
| 9 mm pitches | 26 |
| Total number of 18 mm modules | 26 |
| Power dissipation in W | 50 W |
| [In] rated current | 63 A |
| [Ui] rated insulation voltage | 400 V |
| Type of rail | DIN |
| Mounting plate description | Without mounting plate |
| Cable entry | Cable or tube Removable plates Side pre-cutouts |
| Number of terminal blocks | 1 earth (Quick) with 24 outgoing 1 neutral (Quick) with 24 outgoing |
| Distribution block outgoing | 3 x 25 mm ² for earth |

21 x 4 mm² for earth
3 x 25 mm² for neutral
21 x 4 mm² for neutral

| | |
|---------------------------|--|
| Enclosure material | Back part: technoplastic Front face: technoplastic |
| Colour | Enclosure: white (RAL 9016) Front face: grey (RAL 7004) |
| Targeted country | Czech republic Hungary Russia Greece |
| Embedding depth | 86 mm |
| Internal depth | 84 mm |

Environment

| | |
|--|---|
| Fire resistance | Back part: 650 °C Front face: 650 °C |
| IP degree of protection | IP30 without door IP40 with door |
| IK degree of protection | IK08 without door IK09 with door |
| Overvoltage category | II |
| Ambient air temperature for operation | -25...60 °C |
| Standards | IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3 |

Packing Units

| | |
|-------------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 13.500 cm |
| Package 1 Width | 42.000 cm |
| Package 1 Length | 53.000 cm |
| Package 1 Weight | 3.640 kg |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 31 |
| Package 2 Height | 120.000 cm |
| Package 2 Width | 80.000 cm |
| Package 2 Length | 120.000 cm |
| Package 2 Weight | 124.840 kg |

Offer Sustainability

| | |
|---------------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |


| | |
|-----------------------------|---|
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Halogen content performance | Halogen free product |


Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Recommended replacement(s)

PRA25213 may be replaced by any of the following products:

| | | |
|----|---|--|
| 1x |  | Modular enclosure, PrismaSeT XS, flush, 2 x 13 modules, 1 earth + 1 neutral terminal blocks, plain white door LV SXN213 |
|----|---|--|

| | | |
|----|---|---|
| 1x |  | Modular enclosure, PrismaSeT XS, flush, 2 x 13 modules, 1 earth + 1 neutral terminal blocks, transparent smoked door LV SXP213 |
|----|---|---|
