

Product data sheet

Specifications



Pragma flush enclosure - IP40 - 1 x 13 modules - without door

PRA25113

! To be discontinued on: 30 June 2023

! To be discontinued

Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	366 mm wall: 396 mm outside:
Height	330 mm wall: 360 mm outside:
Depth	86 mm wall: 21 mm outside:
Nb of 18 mm modules per row	13
Nb of horizontal rows	1
Electrical insulation class	Class II Double insulation
Provided equipment	2 x terminal block 1 x identification label 1 x marking kit 1 x blanking plate strip
Type of door	Without

Complementary

Enclosure mounting	Flush
9 mm pitches	26
Total number of 18 mm modules	13
Power dissipation in W	34 W
[In] rated current	63 A
[Ui] rated insulation voltage	400 V
Type of rail	DIN
Mounting plate description	Without mounting plate
Cable entry	Cable or tube Side pre-cutouts Removable plates
Number of terminal blocks	1 earth (Quick) with 14 outgoers 1 neutral (Quick) with 14 outgoers
Distribution block outgoers	3 x 25 mm ² for earth

11 x 4 mm² for earth
3 x 25 mm² for neutral
11 x 4 mm² for neutral

Enclosure material Back part: technoplastic
Front face: technoplastic

Colour Enclosure: white (RAL 9016)
Front face: grey (RAL 7004)

Targeted country Hungary
Czech republic
Russia
Greece

Embedding depth 86 mm

Internal depth 84 mm

Environment

Fire resistance Back part: 650 °C
Front face: 650 °C

IP degree of protection IP30 without door
IP40 with door

IK degree of protection IK08 without door
IK09 with door

Overvoltage category II

Ambient air temperature for operation -25...60 °C

Standards IEC 60670-1
IEC 60670-24
IEC 61439-1
IEC 61439-3

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1 1

Package 1 Height 13.500 cm

Package 1 Width 42.000 cm

Package 1 Length 38.000 cm

Package 1 Weight 2.250 kg

Unit Type of Package 2 P12

Number of Units in Package 2 42

Package 2 Height 120.000 cm

Package 2 Width 80.000 cm

Package 2 Length 120.000 cm

Package 2 Weight 120.360 kg

Offer Sustainability

Sustainable offer status Green Premium product

REACH Regulation [REACH Declaration](#)

REACH free of SVHC Yes

EU RoHS Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

Toxic heavy metal free Yes

Mercury free Yes

China RoHS Regulation [China RoHS declaration](#)
Pro-active China RoHS declaration (out of China RoHS legal scope)

RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)