

# Product data sheet

Specifications



## Auxiliary contacts block, TeSys GC & GY, 2NO, 250V, Right side mounting

GAC0531

### Main

Range	TeSys
Device short name	GAC0
Product or component type	Auxiliary contact block
Product compatibility	TeSys GY TeSys GC
Mounting location	Right side
Pole contact composition	2 NO
[Ue] rated operational voltage	250 V
[Ith] conventional free air thermal current	5 A (at 50 °C)

### Complementary

[Ui] rated insulation voltage	500 V conforming to IEC 60947-5 500 V conforming to VDE 0110
Mechanical durability	1 Mcycles
Connections - terminals	Screw clamp terminals2.5 mm <sup>2</sup> solid Screw clamp terminals2.5 mm <sup>2</sup> flexible
Tightening torque	0.8 N.m - on screw clamp terminals
Height	81 mm
Width	8.75 mm
Depth	60 mm
Net weight	0.016 kg

### Environment

Standards	IEC 60947-5
Product certifications	CEBEC OVE VDE NF-USE
IP degree of protection	IP20 conforming to VDE 0106
Protective treatment	TC
Ambient air temperature for operation	-5...50 °C

Ambient air temperature for storage	-40...70 °C
Operating altitude	<= 3000 m without derating

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	7.5 cm
Package 1 Length	8.6 cm
Package 1 Weight	44.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	8.0 cm
Package 2 Width	9.5 cm
Package 2 Length	23.0 cm
Package 2 Weight	491.0 g
Unit Type of Package 3	S03
Number of Units in Package 3	80
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	4.451 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	18 months
----------	-----------

## Recommended replacement(s)