

PRODUCT-DETAILS

DS201 C10 AC30

DS201 C10 AC30 Residual Current Circuit Breaker with Overcurrent Protection



General Information

| | |
|-----------------------|--|
| Extended Product Type | DS201 C10 AC30 |
| Product ID | 2CSR255080R1104 |
| EAN | 8012542049418 |
| Catalog Description | DS201 C10 AC30 Residual Current Circuit Breaker with Overcurrent Protection |
| Long Description | The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA). |

Technical

| | |
|---|----------------------------------|
| Standards | IEC/EN 61009-1, IEC/EN 61009-2-1 |
| Tripping Characteristic | C |
| Type of Residual Current | AC type |
| Rated Voltage (U_r) | 230 V |
| Rated Operational Voltage | 230 / 240 V AC |
| Rated Insulation Voltage (U_i) | 500 V |
| Test Voltage (U_t) | 170 ... 264 V |
| Dielectric Test Voltage | 2 kV |
| Primary Rated Impulse Withstand Voltage | 4 kV |
| Input Voltage Type | AC |
| Rated Current (I_n) | 10 A |

| | |
|---|---|
| Rated Residual Current | 30 mA |
| Rated Short-Circuit Capacity | 6 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | 10 kA |
| Rated Residual Breaking Capacity ($I_{\Delta m}$) | EN 61009-1 6000 A IEC 61009-1 6000 A |
| Rated Conditional Short-Circuit Current (I_{nc}) | 10 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | 7.5 kA |
| Maximum Surge Current | 0 kA |
| Leakage Current Type | AC |
| Frequency (f) | 50/60 Hz |
| Rated Frequency (f) | 50 ... 60 Hz |
| Power Loss | 1.8 W |
| Power Supply Connection | Arbitrary |
| Contact Position Indication | Red ON / Green OFF |
| Energy Limiting Class | 3 |
| Electrical Endurance | 10000 cycle |
| Mechanical Endurance | 20000 cycle |
| Number of Poles | 2 |
| Number of Protected Poles | 1 |
| Number of Modular Spacings per DIN Rail | 2 |
| Fault Indication | Blue flag on toggle |
| Operating Characteristic | Instantaneous |
| Overvoltage Category | III |
| Position of Neutral Terminals | Right |
| Tightening Torque | 2.8 N·m |
| Accessory Type | Auxiliary contact, Signal contact / auxiliary contact, Shunt trip, Auxiliary contact for bottom fitting, Overvoltage release, Motor operating device |
| Actuator Type | Toggle - Insulation group II, Black RAL 9005, sealable in ON-OFF positions |
| Housing Type | Insulation group I - II, RAL 7035 |
| Mounting Type | on DIN rail EN 60715 (35mm) by means of mounting clip |
| Release Type | C |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Mounting Position | Any |
| Accessories Available | Yes |
| Number of Batteries | 0 |
| Cable Size | 25 mm ² |
| Connecting Capacity | Busbar 10 ... 10 mm ² Stranded 0.75 ... 25 mm ² Flexible with Ferrule 0.75 ... 16 mm ² Flexible 0.75 ... 16 mm ² |
| Wire Stripping Length | 12 mm |
| Terminal Type | Screw Terminals |

Environmental

| | |
|-------------------------|-----------------------|
| Ambient Temperature | -25...55 °C |
| Ambient Air Temperature | Operation -25...55 °C |

| | |
|---|---|
| Reference Ambient Air Temperature | 30 °C |
| Degree of Protection | Terminals IP20 Housing IP40 |
| Pollution Degree | 2 |
| Environmental Conditions | 28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 % |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 0.1 mm or 1 g - 20 cycles at 5...150...5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |
| Environmental Information | 2CSC422002K2701 |

Technical UL/CSA

| | |
|-------------------------------------|--------|
| Short-Circuit Current Rating (SCCR) | 0.03 A |
|-------------------------------------|--------|

Dimensions

| | |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 2 |
| Product Net Width | 0.035 m |
| Product Net Height | 0.085 m |
| Product Net Depth / Length | 0.069 m |
| Product Net Weight | 0.200 kg |
| Built-In Depth (t ₂) | 69 mm |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 40 mm |
| Package Level 1 Height | 106 mm |
| Package Level 1 Depth / Length | 80 mm |
| Package Level 1 Gross Weight | 225 g |
| Package Level 1 EAN | 8012542049418 |
| Package Level 2 Units | box 5 piece |
| Package Level 2 Width | 200 mm |
| Package Level 2 Height | 106 mm |
| Package Level 2 Depth / Length | 80 mm |
| Package Level 2 Gross Weight | 1125 g |
| Package Level 2 EAN | 8012542573814 |

Ordering

| | |
|------------------------|------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363010 |
| Country of Origin | Italy (IT) |

Certificates and Declarations (Document Number)

| | |
|-----------------------------------|------------------------------------|
| ABS Certificate | 9AKK107991A2823 |
| CB Certificate | 9AKK107492A6060 |
| CCC Certificate | 9AKK107492A6067 |
| Declaration of Conformity - CE | 9AKK106713A5588 |
| DNV GL Certificate | 9AKK107680A3457 9AKK107680A3456 |
| EAC Certificate | 9AKK107492A6071 9AKK107991A7755 |
| Environmental Information | 2CSC422002K2701 |
| GOST Certificate | 9AKK107992A1640 |
| Instructions and Manuals | 9AKK107492A6006 |
| ÖVE Certificate | 9AKK107492A6085 |
| RMRS Certificate | 9AKK107680A3454 9AKK107680A3455 |
| RoHS Information | 2CSC422002K2701 |

Popular Downloads

| | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107492A6187 |
| Instructions and Manuals | 9AKK107492A6006 |
| EPLAN Macro | 9AKK107680A0597 |

Classifications

| | |
|----------------------------|--|
| ETIM 7 | EC000905 - Earth leakage circuit breaker |
| ETIM 8 | EC000905 - Earth leakage circuit breaker |
| EPLAN Catalog Tree | Electrical engineering / Protection devices / Ground fault current circuit breaker |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85363010 |
| eClass | V11.0 : 27142207 |
| Object Classification Code | F |

Accessories

| Identifier | Description | Type | Quantity | Unit Of Measure |
|-----------------|--------------------------------------|------------|----------|-----------------|
| 2CDS200912R0001 | S2C-H6R Auxiliary Contact | S2C-H6R | 1 | piece |
| 2CDS200922R0001 | S2C-S/H6R Signal / Auxiliary Contact | S2C-S/H6R | 1 | piece |
| 2CDS200946R0001 | S2C-H6-11R Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0002 | S2C-H6-20R Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CDS200946R0003 | S2C-H6-02R Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200970R0031 | S2C-H01 Auxiliary Contact | S2C-H01 | 1 | piece |
| 2CDS200970R0032 | S2C-H10 Auxiliary Contact | S2C-H10 | 1 | piece |
| 2CSS200910R0005 | S2C-OVP1 Overvoltage release | S2C-OVP1 | 1 | piece |
| 2CSS200933R0011 | F2C-A1 Shunt trip | F2C-A1 | 1 | piece |
| 2CSS200933R0012 | F2C-A2 Shunt trip | F2C-A2 | 1 | piece |
| 2CSS200993R0005 | S2C-OVP2 Overvoltage release | S2C-OVP2 | 1 | piece |
| 2CSS203997R0013 | S2C-CM2/3 Motor operating device | S2C-CM2/3 | 1 | piece |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

