

PRODUCT-DETAILS

TA25DU-32

TA25DU-32 Thermal Overload Relay 24 ... 32 A



genel Bilgi

Geniřletilmiř Ürün Türü	TA25DU-32
Ürün Kimlięi	1SAZ211201R1053
EAN	4013614216640
Katalog Açıklaması	TA25DU-32 Thermal Overload Relay 24 ... 32 A

Uzun Açıklama

The TA25DU-32 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10A. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP- and Test function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.

Ordering

Minimum Sipariř Miktarı	1 piece
Gümrük Tarifesi numarası	85364900

Popular Downloads

Talimatlar ve Kılavuzlar	2CDC106031M6802
Talimatlar ve Kılavuzlar (Bölüm 2)	1SAC200017M0002
Time-Current Characteristic Curve	1SAZ200501F0018

Boyut Şeması

1SAZ200402F0001

Dimensions

Ürün Net Geniřliđi	44 mm
Ürün Net Yüksekliđi	94 mm
Ürün Net Derinlik / Uzunluk	94 mm
Ürün Net Ađırlıđı	0.2 kg

Technical

Setting Range	24 ... 32 A
Nominal Çalışma Gerilimi	Auxiliary Circuit 440 V DC Auxiliary Circuit 500 V AC Main Circuit 690 V AC Main Circuit 440 V DC
Anma Çalışma Akımı (I_e)	32 A
Nominal Frekans (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 60 Hz Main Circuit 50 Hz Main Circuit DC
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV Main Circuit 6 kV
Rated Insulation Voltage (U_i)	690 V
Kutup Sayısı	3
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Protected Poles	3
Conventional Free-air Thermal Current (I_{th})	Auxiliary Circuit NC 10 A Auxiliary Circuit NO 6 A
Rated Operational Current AC-15 (I_e)	(120 V) NC 3 A (120 V) NO 1.5 A (240 V) NC 3 A (240 V) NO 1.5 A (400 V) NC 1.9 A (400 V) NO 1 A (440 V) NC 1 A (440 V) NO 1 A (500 V) NC 1 A (500 V) NO 1 A
Rated Operational Current DC-13 (I_e)	(125 V) NC 0.25 A (125 V) NO 0.25 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.12 A (250 V) NO 0.04 A (60 V) NC 0.25 A (60 V) NO 0.25 A
Koruma Derecesi	Housing IP20 Main Circuit Terminals IP10
Pollution Degree	3
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible 1/2x 0.75 ... 2.5 mm ² Rigid 1/2x 0.75 ... 4 mm ²
Connecting Capacity Main Circuit	Flexible with Ferrule 1x 1.5 ... 6 mm ² Flexible 1x 1.5 ... 6 mm ² Rigid 1x 1.5 ... 10 mm ²

Sıkma Torku	Auxiliary Circuit 1 ... 1.3 N-m Main Circuit 2.5 ... 3.2 N-m
Wire Stripping Length	Auxiliary Circuit 9 mm Main Circuit 15 mm
Recommended Screw Driver	Auxiliary Circuit Pozidriv 1 Main Circuit Pozidriv 2
Power Loss	at Rated Operating Conditions per Pole 1.8 ... 3.3 W
Şuna Uygun	A9 A12 A16 A26 A30 A40 AL9 AL12 AL16 AL26 AL30 AL40
Standartlar	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Contact Rating UL/CSA	(NC:) B600 (NO:) C300
Connecting Capacity Main Circuit UL/CSA	Flexible 1x 10-8 AWG Stranded 1x 10-8 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-14 AWG Stranded 1/2x 18-14 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 12 in-lb Main Circuit 20 in-lb

Environmental

Ortam Hava Sıcaklığı	Operation -25 ... +55 °C Operation Compensated -25 ... +55 °C Storage -40 ... +70 °C
Ambient Air Temperature Compensation	Yes
İzin Verilen Maksimum Çalışma Rakımı	2000 m
IEC 60068-2-27'ye göre Şoka Karşı Direnç	25g / 2 shocks / 13 ms 11 ms Pulse 12g
RoHS Durumu	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Certificates and Declarations (Document Number)

ABS Sertifikası	1SAA941000-0102
BV Sertifikası	1SAA941000-0201
CB Certificate	1SAA941005-2001
CQC Certificate	CQC2015010309808587
Declaration of Conformity - CCC	2020980304001318
Uygunluk Beyanı - CE	1SAD938518-0043
Declaration of Conformity - UKCA	1SAD938501-1043

DNV Sertifikası	1SAA941000-0304
DNV GL Certificate	1SAA941000-0304
EAC Certificate	1SAA941002-2702
GL Sertifikası	1SAA941000-0304
Talimatlar ve Kılavuzlar	2CDC106031M6802
Talimatlar ve Kılavuzlar (Bölüm 2)	1SAC200017M0002
LR Sertifikası	1SAA941000-0504
REACH Declaration	2CMT2021-006202
RMRS Sertifikası	1SAA941000-0704
RoHS Bilgileri	2CMT2021-006277
Time-Current Characteristic Curve	1SAZ200501F0018
UL Sertifikası	E48139-19970507

Container Information

Paket Seviye 1 Birimler	1 piece
Paket Düzey 1 Genişlik	98 mm
Paket Seviye 1 Yükseklik	82 mm
Paket Seviye 1 Derinlik / Uzunluk	47 mm
Paket Seviye 1 Brüt Ağırlık	0.22 kg
Paket Düzey 1 EAN	4013614216640
Paket Seviye 2 Birimler	48 piece
Paket Düzey 2 Genişlik	280 mm
Paket Seviye 2 Yükseklik	210 mm
Paket Seviye 2 Derinlik / Uzunluk	395 mm
Paket Seviye 2 Brüt Ağırlık	10.946 kg
Paket Seviye 2 EAN	4013614442049

Classifications

Nesne Sınıflandırma Kodu	F
ETIM 4	EC000106 - Thermal overload relay
ETIM 5	EC000106 - Thermal overload relay
ETIM 6	EC000106 - Thermal overload relay
ETIM 7	EC000106 - Thermal overload relay
ETIM 8	EC000106 - Thermal overload relay
eSınıf	V11.0 : 27371501
UNSPSC	39122330
IDEA Granüler Kategori Kodu (IGCC)	5366 >> Thermal overload relay
E-Number (Finland)	3709380

katagori

Low Voltage Products and Systems → Control Products → Contactors → Thermal Overload Relays

