



## Plana: 1P 10AX 2-way switch white

---

**14004**

Plana / Devices / Basic devices

### **1P 10AX 2-way switch white**

1P 10 AX 250 V~ 2-way switch, lightable, replaceable button, white. Max 100 W for self-ballasted lamps (IEC 60669-1:2017)

- Modular series for flush mounting and surface mounting
- The efficient, energy-saving LED backlighting available in several colours makes the controls visible even in the dark, while the laser-engraved or customised symbols always clearly indicate the various functions
- Vimar patented Plack Clack® fixing system, which gives the lighting device added strength once the cover plate is installed
- Polished and shiny dirt-proof surfaces



### **Product Status**

3 - Active

### **Minimum order quantity**

50 NR

## You may also be interested in



00936.250.W - LED unit 250V  
0,35W white



00931 - Pre-wired LED unit  
110-250V 0,5W amber



00936.250.A - LED unit 250V  
0,35W amber



00936.250.G - LED unit 250V  
0,35W green




00936.250.R - LED unit 250V  
0,35W red




00936.250.B - LED unit 250V  
0,35W light blue


## Drawings



Space view



Backside view



3D View

## Gallery



## Technical data

- **Class group:** Domestic switching devices
- **Class:** Installation switch
- **Wiring system:** Two-way switch
- **Method of operation:** Rocker/button
- **Assembly arrangement:** Modular device for domestic switching devices
- **Number of modules (module system):** 1
- **Push button switch:** Yes
- **Number of rockers:** 1
- **Mounting method:** Flush mounted (plaster)
- **Type of fastening:** Engage (snap)
- **With mounting plate:** No
- **Material:** Plastic
- **Material quality:** Thermoplastic
- **Halogen free:** Yes
- **Surface protection:** Untreated
- **Surface finishing:** Glossy
- **Colour:** White
- **RAL-number (similar):** 9003
- **Label space/information surface:** Yes
- **Illumination:** Optional
- **Function lighting:** Control and orientation
- **Type of lighting:** LED exchangeable
- **Suitable for degree of protection (IP):** IP40
- **Nominal voltage:** 250 v
- **Rated current:** 10,00 A
- **Feedback-signal contact:** No
- **Connection type:** Screwed terminal
- **Washing machine switch:** No
- **Width of device:** 22,30 mm
- **Height of device:** 49,00 mm
- **Depth of device:** 38,40 mm
- **Built-in depth:** 24,00 mm

## Certifications

- 00. CE Marking - EU
- 01. IMQ - Italy
- 07. INGCER - Chile
- 10. EAC Eurasian Customs Union
- 14. TSE - Turkey ([download](#))
- 15. CCC - China ([download](#))
- 19. NOM - Mexico
- 28. NSW - Australia ([download](#))
- 29. QCERT - Colombia
- 31. TISI - Thailand
- 37. Marking - Morocco
- 43. UKCA mark - Great Britain
- 92. RoHS UAE
- 96. Electrotechnical expert ([download](#))
- 99. WEEE Directive ([download](#))

## Packaging



**Code** 8007352106390  
**Quantity** 1 NR  
**Dim.** 4.1x2.8x5.3 [cm]  
**Weight** 28.8 [g]



**Code** 8007352106406  
**Quantity** 50 NR  
**Dim.** 21.6x11.6x14.3 [cm]  
**Weight** 1,538 [g]



**Code** 8007352263154  
**Quantity** 500 NR  
**Dim.** 57.5x22.5x30 [cm]  
**Weight** 15,836 [g]

## Legal

Vimar reserves the right to change at any time and without notice the characteristics of the products reported. Installation should be carried out by qualified staff in compliance with the current regulations regarding the installation of electrical equipment in the country where the products are installed. For the terms of use of the information on the product info sheet see [Conditions of Use](#).